

The **PX-1000** series is available in Zero U (vertical mount) and 1U (horizontal mount) form factors with a wide variety of NEMA, IEC and other plugs and receptacles, including models which support high power distribution such as 400V. Precise power information can be monitored, and the PX-1000 configured, via a user-friendly Web browser GUI or command line interface. Power information is also displayed at the PDU locally. Security is ensured with up to 256-bit encryption, strong passwords and advanced authorization options, including permissions, LDAP/S and Active Directory. Plus the PX-1000 series is fully compatible with Raritan's Power IQ energy management software solutions.

To find the PDU that best fits your needs, choose your selected model from the table below.

VAC	Outlets	Rack Units	Amps Per Phase					
			≤16	20	30	32	50	60+
120	8	1	PX2-1145R	PX2-1146R , PX2-1147R				
120	24	Zero		PX2-1474 , PX2-1475 , PX2-1802				
208	8	1	PX2-1148R	PX2-1176R , PX2-1180R	PX2-1200R			
208	24	Zero		PX2-1480 , PX2-1482	PX2-1497			
208	36	Zero			PX2-1841			
230	8	1	PX2-1190R					
230	24	Zero	PX2-1486			PX2-1493		
240	8	1	PX2-1190A1R , PX2-1190A2R , PX2-1190A3R , PX2-1486A4					
240	24	Zero	PX2-1486A4	PX2-1486A1 , PX2-1486A2 , PX2-1486A3		PX2-1493A1 , PX2-1493A2		
3PH 208	24	Zero		PX2-1508				PX2-1551
3PH 208	36	Zero			PX2-1724 , PX2-1725 , PX2-1721			
3PH 208	45	Zero			PX2-1955			
3PH 400	24	Zero			PX2-1629			
3PH 400	36	Zero			PX2-1731	PX2-1730 , PX2-1730A1 , PX2-1730A2		

The **PX-2000** series is available in Zero U (vertical mount) and 1U (horizontal mount) form factors with a wide variety of NEMA, IEC and other plugs and receptacles, including models which support high power distribution such as 400V. The PX-2000 supports individual outlet switching. Precise power information can be monitored, and the PX-2000 configured, via a user-friendly Web browser GUI or command line interface. Power information is also displayed at the PDU locally. Security is ensured with up to 256-bit encryption, strong passwords and advanced authorization options, including permissions, LDAP/S and Active Directory. Plus the PX-2000 series is fully compatible with Raritan's Power IQ energy management software solutions.

To find the PDU that best fits your needs, choose your selected model from the table below.

VAC	Outlets	Rack Units	Amps Per Phase					
			≤16	20	30	32	50/60+	
120	8	1	PX2-2142R PX2-2145R PX2-2162R	PX2-2146R PX2-2147R PX2-2166R				
120	24	Zero		PX2-2474 PX2-2475 PX2-2475C PX2-2476 PX2-2802	PX2-2492			
208	8	1	PX2-2148R	PX2-2176R PX2-2180R				
208	24	Zero		PX2-2480 PX2-2482	PX2-2496 PX2-2497			
208	36	Zero						
230	8	1						
230	24	Zero						
240	8	1	PX2-2190R PX2-2190CR PX2-2190A4R	PX2-2190A1R PX2-2190A2R PX2-2190A3R				
240	24	Zero	PX2-2486A4	PX2-2486 PX2-2486C PX2-2486A1 PX2-2486A2 PX2-2486A3		PX2-2493 PX2-2493A1 PX2-2493A2 PX2-2500 PX2-2500A1 PX2-2500A2		
240	36	Zero						
3PH 208	24	Zero		PX2-2510 PX2-2511	PX2-2522 PX2-2523			
3PH 208	36	Zero		PX2-2735 PX2-2736	PX2-2724 PX2-2725			
3PH 400	24	Zero	PX2-2516	PX2-2627	PX2-2633	PX2-2530 PX2-2530A1 PX2-2530A2		
3PH 400	36	Zero	PX2-2732	PX2-2737	PX2-2731	PX2-2730 PX2-2730A1 PX2-2730A2		

The **PX-3000** series is available in 1U (horizontal mount) form factors with AC terminal strips, IEC C-20 plugs and IEC C-19 receptacles. Precise power information can be monitored, and the PX-3000 configured, via a user-friendly Web browser GUI or command line interface. Power information is also displayed at the PDU locally. Security is ensured with up to 256-bit encryption, strong passwords and advanced authorization options, including permissions, LDAP/S and Active Directory. Plus the PX-3000 series is fully compatible with Raritan's Power IQ energy management software solutions.

To find the PDU that best fits your needs, choose your selected model from the table below.

VAC	Lines	Rack Units	Amps Per Phase			
			16	20	30	32
100-240	2	1U	PX-3211 , PX-3220	PX-3211 , PX-3220	PX-3220	PX-3220
100-240	4	1U	PX-3411 , PX-3420 , DPXR4X1A-16NP	PX-3411 , PX-3420	PX-3420 , PX-3423	PX-3420
3PH 380 - 415V	1	Zero			PX2-3172	PX2-3172
3PH 190 - 415	2	1U			PX-3270	PX-3270
3PH 190 - 415	3	1U			PX-3370	PX-3370

Note 1: PX-3211 and PX-3411 operate at either 16A or 20A depending on the cord set chosen.

Note 2: PX-3220 and PX-3420 operate at up to 40A (32A rated) per line depending on the wiring in the data center.

The **PX-4000** series is available in Zero U (vertical mount) and 1U and 2U (horizontal mount) form factors with a wide variety of NEMA, IEC and other plugs and receptacles, including models which support high power distribution such as 400V. Precise power information can be monitored, and the PX-4000 configured, via a user-friendly Web browser GUI or command line interface. Power information is also displayed at the PDU locally. Security is ensured with up to 256-bit encryption, strong passwords and advanced authorization options, including permissions, LDAP/S and Active Directory. Plus the PX-4000 series is fully compatible with Raritan's Power IQ energy management software solutions.

To find the PDU that best fits your needs, choose your selected model from the table below.

VAC	Outlets	Rack Units	Amps Per Phase				
			20	30	32	50	60+
208	4	1U		PX-4080T			
208	8	1U		PX-4198			
208	16	Zero		PX-4384			
208	24	Zero		PX-4496			
3PH 208	6	Zero				PX-4100 , PX-4322	PX-4102
3PH 208	12	Zero				PX-4316 , PX-4320	PX-4320
3PH 208	18	Zero				PX2-4951YV-E2	PX2-4941
3PH 208	24	Zero	PX2-4508	PX-4520 , PX-4521 , PX-4522 ,		PX-4532 , PX-4534 , PX-4535	

				PX-4523 , PX-4524 , PX2-4525			
3PH 208	36	Zero		PX2-4725			
3PH 230	24	Zero					PX-4551
3PH 230	12	2U					PX-4301
3PH 240	16	Zero			PX-4820 , PX-4820A1 , PX-4820A2		
3PH 400	6	Zero		PX-4120	PX-4104 , PX-4104A1 , PX-4104A2		
3PH 400	12	Zero		PX-4621 , PX-4633	PX-4307 , PX-4530		
3PH 400	18	Zero			PX2-4507		
3PH 400	18	2U				PX2-4913U	
3PH 400	24	Zero		PX-4630	PX-4530 , PX-4917 , PX-4917A1 , PX-4917A2		
3PH 400	36	Zero			PX2-4704U		

The PX-5000 series is available in Zero U (vertical mount) and 1U and 2U (horizontal mount) form factors with a wide variety of NEMA, IEC and other plugs and receptacles, including models that support high power distribution such as 400V. Precise power information can be monitored, and the PX-5000 configured, via a user-friendly Web browser GUI or command line interface. Power information is also displayed at the PDU locally. Security is ensured with up to 256-bit encryption, strong passwords and advanced authorization options, including permissions, LDAP/S and Active Directory®. Plus the PX-5000 series is fully compatible with Raritan's Power IQ energy management software solutions.

To find the PDU that best fits your needs, choose your selected model from the table below.

[16-32 Amps Per Phase Models](#) | [50-60 Amps Per Phase Models](#)

VAC	Outlets	Rack Units	Amps Per Phase			
			16	20	30	32
120	8	1	DPXR8-15 , DPCR8-15-J	DPXR8-20 , DPXR8-20L , PX-5812		
120	12	Zero	DPXS12-15	DPXS12-20 , DPXS12-20L , DPCS12-20L-J	DPCS12-30L , DPXS12-30L , DPXS12-30L-J	
120	20	Zero		DPCS20-20 , DPXS20-20 , DPXS20-20L , DPXS20-20L-J	DPXS20-30L , DPCS20-30L-J	
120	20	2		DPXR20-20 , DPXR20-20L	DPXR20-30L	

120	24	Zero		PX-5802T		
3PH 120/ 208	24	Zero		PX2-5561	PX-5652	
3PH 120/ 208	30	Zero			PX2-5660	
208	6	2			PX-5810	
208	8	1		DPXR8A-20L6, DPCR8A-20L6- J, PX-5192C	PX-5198	
208	16	Zero			PX-5384	
208	20	Zero		DPXS20A-20L6	DPCS20A-30L6, DPXS20A- 30L6, DPXS20A- 30L6-J, PX-5464, PX-5464T	
208	20	2		DPXR20A- 20L6	DPXR20A-30L6	
208	24	Zero			PX-5496	
230	8	1	DPXR8A-16			PX-5170
230	12	Zero	DPXS12A-16			DPXS12A-32, PX-5297
230	16	Zero	PX-5367			PX-5397
230	20	Zero	DPXS20A-16, DPXS20A- 16AU-M			DPXS20A-32, PX-5469T, PX-5469, PX-5469A2T
230	20	2	DPXR20A-16			DPXR20A-32
230	24	Zero	DPXS24A-16T			
240	8	1	DPXR8A-15AU	DPXR8A-20AU		
240	12	Zero		DPXS12A- 20AU		DPXS12A- 32AUA
240	16	Zero				PX-5820, PX-5820A1, PX-5820A2
240	20	Zero		DPXS20A- 20AU		DPXS20A- 32AUA, PX-5469A2T
240	24	Zero		PX-5635		PX-5501
3PH 208	6	2			PX-5119	
3PH 208	18	Zero			PX-5902T, PX-5924	
3PH 208	24	Zero		PX-5508, PX- 5510	PX-5520, PX-5522, PX-5523, PX-5524, PX-5525	
3PH 230	12	2U				
3PH	24	Zero				

230						
3PH 400	12	Zero	PX-5314, PX-5315		PX-5616	PX-5318, PX-5318A2
3PH 400	12	2				PX-5318A2
3PH 400	18	Zero				PX-5341
3PH 400	24	Zero	PX-5628I		PX-5630, PX-5633, PX-5550	PX-5528, PX-5530, PX-5917, PX-5917A1, PX-5917A2
3PH 400	36	Zero			PX-5550	
VAC	Outlets	Rack Units	Amps Per Phase			
			50		60	
3PH 208	6	2	PX2-5940			
3PH 208	18	Zero			PX2-5941V	
3PH 208	24	Zero	PX-5532, PX-5534, PX-5535			
3PH 230	12	2U			PX-5301	
3PH 230	24	Zero			PX-5551	
3PH 400	12	Zero				
3PH 400	12	2				
3PH 400	18	Zero				
3PH 400	24	Zero				
3PH 400	36	Zero				