2.5" SATA III SSD 240S Series





The Cactus Technologies 2.5" SATA III SSD - 240S Series is a high capacity solid state flash memory device which complies with the serial ATA 3.1 specifications, ATA-8 ACS2 command set compatible and can functionally replace a SATA Hard Disk Drive in any application. Cactus Technologies 2.5" SATA III SSDs provide up to 1TB of formatted storage capacity.

CACTUS SATA III SSD FEATURES

- → INDUSTRY STANDARD 2.5" SATA III SSD FORM FACTOR
- SSD CAPACITIES
 - 16GB to 512GB (7mm height)
 - 1TB (9.5mm height)
- → SUPPORTS SATA 1.5/3.0/6.0GBPS
- COMPLIANT WITH:
 - Serial ATA 3.1 Spec
 - ANSI ATA-8 ACS2 Command Set
- → 5.0V OPERATION
- → SUPPORTS NCQ W/MAX QUEUE DEPTH OF 32
- → ATA SECURITY FEATURE SET
- → SUPPORTS TRIM FEATURE
- SMART LIFE CYCLE ANALYSIS
- → SOLID STATE DESIGN
- → RELIABILITY
 - High Data Reliability
 - High Shock & Vibration Tolerances
- 200K HOUR MTBF
- 2-YEAR WARRANTY



PERFORMANCE

Read Data Transfer Rate up to 560 MB/sec

Write Data Transfer Rate up to 460 MB/sec



RELIABILITY

- Wear Leveling
- · Error Checking & Correction
- Less Than 1 Error in 10¹⁴ Bits Read
- MTBF 200,000 Hours



ENVIRONMENTAL & POWER

Operating Temperature Range Standard 0°C to 70°C Extended -40°C to 85°C



POWER CONSUMPTION

5.0V

Read 520mA

Write 850mA

Sleep 95mA



SHOCK & VIBRATION

Shock 3,000G Vibration 20G peak-to-peak

2.5" SATA III SSD 240S Series





COMMERCIAL GRADE 2.5" SATA III SSD

| → INTERFACE | ANSI ATA-8 ACS2; Serial ATA 3.1 Spec. | |
|-------------------------------|---------------------------------------|---|
| → INTERFACE TRANSFER RATE | 6.0Gb/sec | |
| → POWER REQUIREMENT | DC Input Voltage | 5.0V ± 10% |
| | Idle | 95mA |
| | Read | 520mA |
| | Write | 850mA |
| → ENVIRONMENTAL SPECIFICATION | Standard Temperature | 0°C to 70°C |
| | Extended Temperature | -40°C to 85°C |
| | Humidity | 8-95%, non-condensing |
| | Acoustic Noise | 0dB |
| | Vibration | 20G peak to peak max. |
| | Shock | 3000G max. |
| | Altitude | 100,000 feet max. |
| → RELIABILITY AND MAINTENANCE | Endurance | 100,000 erase cycles per block |
| | MTBF | 200,000 Hours |
| | Data Reliability | less than 1 Error in 10 ¹⁴ bits read |
| → MEMORY CAPACITY | 16GB to 1TB | |



Cactus USA

Email: americas@cactus-tech Tel: (512) 775 0746 Cactus Technologies® Limited

Email: info@cactus-tech.com

Email: info@cactus-tech.com Tel: (852) 2797 2261



