CACTUS TECHNOLOGIES

Secure Digital® SDChip (SD) 806 Series





The Cactus Technologies Secure Digital® SDChip (SD) - 806 Series is a low capacity solid-state flash memory product that complies with the Secure Digital Card Association (SDA) standard. Cactus SDChips provide up to 4GB (Class 6) of formatted storage capacity and are designed to be used in applications which require reliable, high performance solid state storage in a high shock & vibration environment.

CACTUS SDCHIP FEATURES

- → INDUSTRY STANDARD SDA VERSION 1.1 AND 2.0 SUPPORT
- → CARD CAPACITIES
 - 128MB to 4GB
- **→ INTERFACE SUPPORTS**
 - SD Interface
 - SPI Mode
- **→ VOLTAGE RANGE**
 - 2.7V to 3.6V
- → TRACEABILITY ELECTRONIC CODE
- → SOLID STATE DESIGN
 WITH NO MOVING PARTS
- → INDUSTRY LEADING
 - Data Reliability
 - Shock & Vibration
 - Operating Temp Range
 - Data Transfer Rates
- → ZERO DB NOISE
- → 4-MILLION HOUR MTBF
- → 5-YEAR WARRANTY



PERFORMANCE

Read Data Transfer Rate up to 20MB/sec

Write Data Transfer Rate up to 17MB/sec



RELIABILITY

- Supports Wear Leveling
- Error Checking & Correction
- Less Than 1 Error in 10¹⁴ Bits Read
- MTBF 4,000,000 Hours



ENVIRONMENTAL & POWER

Operating Temperature Range Standard -25°C to +85°C Extended -45°C to +90°C



POWER CONSUMPTION

3.3V ± 10% 40mA

Read 40mA Write 75mA Sleep 180uA



SHOCK & VIBRATION

Shock 3000G

Vibration 30G peak-to-peak

Secure Digital® SDChip (SD) 806 Series





INDUSTRIAL GRADE SDCHIP

→ INTERFACE	SD Version 1.1 and Version 2.0	
→ INTERFACE TRANSFER RATE	25MB/sec	
→ POWER REQUIREMENT	DC Input Voltage	3.3V ± 10%
	Sleep	180uA
	Read	40mA
	Write	75mA
● ENVIRONMENTAL SPECIFICATION	Standard Temperature	-25°C to +85°C
	Extended Temperature	-45°C to +90°C
	Humidity	8-95%, non-condensing
	Acoustic Noise	0dB
	Vibration	30G peak to peak max.
	Shock	3000G max.
	Altitude	100,000 feet max.
→ RELIABILITY AND MAINTENANCE	Endurance	2,000,000 erase cycles per block
	МТВГ	4,000,000 Hours
	Data Reliability	less than 1 Error in 10 ¹⁵ bits read
→ CARD CAPACITY	128MB to 4GB	

Cactus Technologies Limited

Suite C, 15/F, Capital Trade Center 62 Tsun Yip Street, Kwun Tong Kowloon, Hong Kong Tel: +852-2797-2277

Email: sales@cactus-tech.com

Cactus USA

3112 Windsor Road
Suite A356
Austin, Texas 78703
Tel: (512) 775-0746
Email: americas@cactus-tech.com

