

# ATP CompactFlash Card Industrial Grade

# Targeted Product Portfolio, Engineered Specifically for Your Mission Critical Applications





CompactFlash cards in the original IDE/PATA interface continue to enjoy wide usage in industrial and embedded environments due to their durability and rugged build.

ATP's industrial CompactFlash cards work best in high-throughput applications requiring speedy transfers of large blocks of data, such as high-definition videos and camera systems.

Industrial temperature-rated CompactFlash cards can operate in critical temperature ranges, from -40°C to 85°C. Superior flash management capabilities such as Advanced Wear Leveling, bad block management, and AutoRefresh technology ensure data integrity, reliability and longevity for a wide range of applications and workloads. ATP's own PowerProtector provides hardware-based protection that prevents data loss or corruption due to power losses or fluctuations.

#### **Key Features**

- Global wear leveling and bad block management
- AutoRefresh technology
- PowerProtector
- Power saving mode
- S.M.A.R.T. support

#### **Applications**

- Portable compution
- Automation
- Industrial PC
- Gaming
- On board data storage



### **Specifications**

Product Name		CompactFlash Card					
Product Line		Premium	Superior				
Naming		1800Pi	1700Sc	1600Sc			
Flash Type		SLC	SLC mode	MLC			
Density		512 MB to 32 GB	8 GB to 16 GB	16 GB to 32 GB			
Performance	Sequential Read up to (MB/s)	61	110	108			
	Sequential Write up to (MB/s)	55	80	46			
Interface		UDMA 0~4	UDMA 0~6				
Operating Temperature		-40°C to 85°C	0°C to 70°C				
Endurance	TBW* (max.)	1,280 TB	128 TB	38 TB			
	DWPD* (max.)	22.4	11.2	1.7			
Reliability	MTBF @ 25°C	>5,000,000 hours	,000 hours >2,000,000 hours				
	Number of Insertions	10,000 minimum					
Dimensions: L x W x H (mm)		36.4 x 42.8 x 3.3					

 $<sup>^{\</sup>ast}$  Under highest Sequential write value. May vary by density, configuration and applications.

Technologies & Add-On Services		Life Monitor	Sudden Power-Off Recovery	Advanced Wear Leveling	AutoRefresh	Dynamic Data Refresh	Industrial Temperature	Anti-Sulfur Resistors	Conformal Coating
Product Line	Premium	•	•	•	•	•	•	Δ	Δ
	Superior	•		•	•	•		Δ	Δ

 $<sup>\</sup>Delta \!\!:\! \textsc{Customization}$  option available on a project basis.

## To learn more about this product, contact your ATP Representative.

ATP Global Footprint

ATP TAIWAN(HQ)

TEL: +886-2-2659-6368 FAX: +886-2-2659-4982 sales-apac@atpinc.com ATP USA

TEL: +1-408-732-5000 FAX: +1-408-732-5055 sales@atpinc.com ATP EUROPE

TEL: +49-89-374-9999-0 FAX: +49-89-374-9999-29 sales-europe@atpinc.com ATP JAPAN

TEL: +81-3-6260-0797 FAX: +81-3-6260-0798 sales-japan@atpinc.com ATP CHINA

TEL: +86-21-5080-2220 FAX: +86-21-9687-0000-026 sales@cn.atpinc.com