

# EF600-115R5

High flow filter fan



This vertical filter fan, EF, with a IP 54 protection degree, is easy to install thanks to its click-in feature. Unnecessary downtime is avoided, since water and dust are prevented from entering the enclosure through the filter, and the reliable fan motor will ensure constant ventilation.



IP 54 | TYPE 12

115 V AC, 50/60Hz

|                            |             |
|----------------------------|-------------|
| Bearing type               | Ball        |
| Connection                 | Spring type |
| Current (A)                | 0.96/1.40   |
| Noise (dB)                 | 64          |
| EF+EFA Air flow (m³/h)     | 445         |
| Connection Type            | 3           |
| Unimpeded air-flow (m³/h)  | 640/653     |
| Filter mat (EN779)         | G3          |
| Filtration efficiency (%)  | 80-90       |
| Service life L10 (40°C)(h) | 40.000      |
| Cut-out (mm)               | 291 × 291   |
| Weight (kg)                | 4.10        |
| Power (W)                  | 110/160     |
| Fuse (A)                   | 6           |
| Item no.                   | EF600-115R5 |

**Description:** Filter fan for forced ventilation. nVent HOFFMAN filter fans save time on installation as they are installed with a click-in system without screws. The hinged front cover can be easily opened for quick and easy filter replacement. The airflow direction and the connection position can easily be changed.

**Material:** Front cover manufactured from injection-moulded thermoplastic, self-extinguishing, UL94V0.

**Temperature range:** -40 °C to +55 °C.

**Protection:** IP 54 | TYPE 12.

**Finish:** RAL 7035.

**Pack quantity:** One fan with filter.