



ATP mSATA Embedded SSD

Targeted Product Portfolio, Engineered Specifically for Your
Mission Critical Applications



Just roughly the size of a business card, ATP's mSATA SSDs offer up to 512 GB capacity and the same speed and efficiency of SATA. They are designed to fit in systems with space constraints and high-performance requirements such as embedded and networking applications.

Two mounting holes keep the mSATA module securely installed, protecting it from shock and vibration. ATP mSATA SSDs are available in industrial temperature ratings for trustworthy performance in sub-freezing or extremely hot settings. Available on select mSATA SSDs is PowerProtector 4, ATP's advanced power loss protection (PLP) technology, which combines hardware and software solutions to prevent data corruption and storage device damage when power glitches, losses and failures occur.

Key Features

- Global wear leveling
- TRIM function support
- AutoRefresh and Idle Clean F/W algorithm
- Firmware live update
- MCU-based Power Protector 4
(May vary by product and project support.)

Applications

- Telecommunications
- Industrial & Embedded
- Gaming & Digital Signage
- Medical & Field Equipment
- Server & Storage
- Ruggedized Tablets



Specifications

Product Name	mSATA			
Product Line	Premium		Superior	
Naming	A800Pi	A700Pi	A600Si	A600Sc
Flash Type	SLC	iTemp pseudo SLC	iTemp MLC	MLC
Density	8 GB to 128 GB	80 GB to 160 GB	16 GB to 64 GB	
Performance	Sequential Read up to (MB/s)	530	560	440
	Sequential Write up to (MB/s)	430	520	80
	Random Read IOPS up to	76,000	94,000	38,400
Interface	SATA III 6 Gb/s			
Operating Temperature	-40°C to 85°C		-40°C to 85°C	0°C to 70°C
Endurance	TBW* (max.)	10,667 TB	6,400 TB	145.5 TB
	DWPD* (max.)	77.9	21.9	3.1
Reliability MTBF @ 25°C	>2,000,000 hours			
Dimensions: L x W x H (mm)	50.8 x 29.85 x 3.5			

Product Name	mSATA		
Product Line	Superior		Value
Naming	A600Si	A600Sc	A600Vc
Flash Type	iTemp 3D TLC	3D TLC	3D TLC
Density	240 GB to 480 GB	120 GB to 480 GB	32 GB to 512 GB
Performance	Sequential Read up to (MB/s)	560	560
	Sequential Write up to (MB/s)	440	420
	Random Read IOPS up to	100,000	72,000
Interface	SATA III 6 Gb/s		
Operating Temperature	-40°C to 85°C	0°C to 70°C	0°C to 70°C
Endurance	TBW* (max.)	1,396 TB	590.8 TB
	DWPD* (max.)	4.0	1.6
Reliability MTBF @ 25°C	>2,000,000 hours		
Dimensions: L x W x H (mm)	50.8 x 29.85 x 3.5	50.8 x 29.85 x 3.5	

* Under highest Sequential write value. May vary by density, configuration and applications.

Technologies & Add-On Services		S.M.A.R.T.	PowerProtector	Advanced Wear Leveling	AutoRefresh	Dynamic Data Refresh	Secure Erase	Industrial Temperature	Anti-Sulfur Resistors	Conformal Coating
Product Line	Premium	●	●	●	●	●	●	●	Δ	Δ
	Superior	●	●	●	●	●	●	Δ	Δ	Δ
	Value	●		●	●	●				

Δ: Customization option available on a project basis.

To learn more about this product, contact your ATP Representative.

ATP Global Footprint

ATP TAIWAN(HQ)

TEL: +886-2-2659-6368
FAX: +886-2-2659-4982
sales-apac@atpinc.com

ATP USA

TEL: +1-408-732-5000
FAX: +1-408-732-5055
sales@atpinc.com

ATP EUROPE

TEL: +49-89-374-9999-0
FAX: +49-89-374-9999-29
sales-europe@atpinc.com

ATP JAPAN

TEL: +81-3-6260-0797
FAX: +81-3-6260-0798
sales-japan@atpinc.com

ATP CHINA

TEL: +86-21-5080-2220
FAX: +86-21-9687-0000-026
sales@cn.atpinc.com